



„Nordmast“ stiklo pluošto vėliavos stiebo matmenys ir specifikacijos

		6m	7m	8m	9m	10m	12m	14m	14m dvigu bas	16m dvigu bas	18m dvigu bas
Stiklo pluošto vamzdžio svoris	kg	9,0	10,0	12,0	14,5	20,5	26,0	44,0	61,0	71,0	81,0
Bendras svoris su plienine įranga	kg	21,0	22,5	24,0	26,0	36,0	41,5	66,0	116,0	126,0	136,0
Viršutinės dalies skersmuo	mm	65	65	65	65	65	65	65	65	65	65
Apatinės dalies skersmuo	mm	120	120	120	120	140	140	140	180	180	180
Stiklo pluošto storis (+/- 0,5 mm)	mm	3,5	3,5	3,5	3,5	4,0	4,0	5,0	5,0	5,0	5,0
Cilindro ilgis	m	1	2	3	4	1	3	5	6	8	10
Plieninio vamzdžio ilgis	mm	500	500	500	500	600	600	1000	1000	1000	1000
Plieninio vamzdžio storis	mm	3,2	3,2	3,2	3,2	4,0	4,0	4,0	5,0	5,0	5,0
Plieninio vamzdžio skersmuo	mm	101	101	101	101	121	121	121	159	159	159
Pamato gylis	mm	800	800	800	900	1000	1200	1200	1400	1500	1500
Pamato skersmuo	mm	300	300	300	300	400	400	500	600	600	600
Betono duobės skersmuo	mm	25	25	25	25	25	25	25	25	25	25
Betono angos gylis	mm	300	300	300	300	400	400	400	500	500	500

Stiklo pluošto dangčio svoris: 0,8 kg, matmenys: 160 * 355 mm.